

Hole	From	To	Length (m)	Au (g/t)
<b>11-CCR-003</b>	0	74.68	74.68	overburden
<b>11-CCR-003</b>	86.97	102.72	15.75	0.48
including	88.5	93	4.5	0.91
<b>11-CCR-021</b>	0	75.29	75.29	overburden
<b>11-CCR-021</b>	75.29	132	56.71	0.5
including	103	105.8	2.8	3.06
<b>11-CCR-023</b>	0	48.77	48.77	overburden
<b>11-CCR-023</b>	74	121.5	47.5	0.35
including	86.5	88	1.5	2.61
and	118	120	2	1.06
<b>11-CCR-023</b>	145	170	25	0.34
<b>11-CCR-023</b>	198.5	253.9	55.4	0.82
including	202.25	204	1.75	3.18
and	243	244.5	1.5	14.65
<b>11-CCR-030</b>	0	85.04	85.04	overburden
<b>11-CCR-030</b>	85.04	177.5	92.46	0.58
including	145.5	153	7.5	4.12
and	150	151.5	1.5	12.15
<b>12-CCR-036</b>	0	69.49		Overburden
	96.93	106	9.07	0.67
including	96.93	99.8	2.87	1.62
<b>12-CCR-036</b>	162.5	187	24.5	0.26
<b>12-CCR-037</b>	0	57.7		Overburden
	48.16	98.03	49.87	0.23
including	48.16	50.52	2.36	0.83
<b>12-CCR-037</b>	137	197	60	0.48
including	165	167	2	1.2
and	172.5	174	1.5	3.54
and	185	187	2	4.68
<b>12-CCR-038</b>	0	76.61		Overburden
	111.7	146.5	34.8	0.35
including	140.29	141.5	1.2	2.92